



DIGITAL SCREEN INTELLINGENT STORAGE LITHIUM BATTERY - SQUARE ALUMINUM SHELL BATTERY


MODEL: CNLFP200-12(DS)-F

NO.:302150061-00043



Plane Chart:


Unit:(mm) Terminal type:(LC4)




Parameter Chart:

Volts		12V
Capacity(25°C)	10 hours rate (20A)	200Ah
Internal Resistance	Full Charged Battery 25°C	≤30mΩ
Capacity Affected By Temperature	40°C	101%
	25°C	100%
	0°C	93%
	-20°C	65%
Residual Capacity (25°C)	Capacity After 3 Months Storage	87%
	Capacity After 6 Months Storage	74%
	Capacity After 12 Months Storage	50%
Charge (Constant Voltage)	Cycle (25°C)	Initial Charging Current Less Than 30A Voltage 14.4~15.0V
	Float (25°C)	Charge Voltage 13.6~13.8V
Discharge Current (25°C)		60A (Max. continuous); 90A (5 Seconds)
Weight (Approx)		19.30Kg


Discharge Current 25°C



Cycle service life in relation to the depth of discharge



Residual Capacity



Constant Current Discharge Characteristics (A, 25°C)

F.V/Time	3.3h	3.6h	4h	5.3h	6.6h	8h	10h	21h
10V	60	55	50	37.5	30	25	20	10

Constant Power Discharge Characteristics (Watt, 25°C)

F.V/Time	3.3h	3.6h	4h	5.3h	6.6h	8h	10h	21h
10V	720	660	600	450	360	300	240	120

Capacity Factors With Different Temperature

Battery Type		-20°C	-10°C	0°C	5°C	10°C	20°C	25°C	30°C	40°C	45°C
Li Battery	12V	65%	82%	93%	95%	97%	100%	100%	100%	101%	102%

★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.

Constant voltage charging characteristics

